


QUMULUS®

Model QUMULUS is a design revolution within security fog. Even with its friendly, elegant and discreet appearance it has the power to drive away evil burglars - even before they get started. Because of the aesthetic, patented design and high quality, QUMULUS is the chosen model for private homes and exclusive offices and shops.



Up to 5 year warranty

European quality - Danish design. QUMULUS comes with a 2 year warranty. Three extra year of warranty online product registration on protectglobal.com/extra-warranty.



Possibility of 2 angled nozzles

QUMULUS comes with a straight nozzle. However it can easily be exchanged with 30° nozzle.



XTRA+ fog fluid

The 0.4 l fog fluid bag can be easily replaced by the user himself without fog fluid spillage. QUMULUS is delivered with 1 bag of XTRA+ fog fluid. XTRA+ is white and dry fog with extended dissipation time.

Features:

- Discharges 400 m³ of fog at full speed in 60 seconds which is sufficient to cover a living room for up to 50 m²
- Flexible adjustment between 140 and 400 m³ to exactly fit the size of the room
- Pulse function for up to 4 min. (effective maintenance of the fog)
- Compatible with any alarm system including ZOLO GSM Alarm System
- Compatible with IPCard, MultiCard and IntelliBox
- Data log memory possible with IntelliSuite
- Integration with all types of alarm systems
- 100 % silent in standby mode
- Prepared for 2 different angled nozzles
- Patented design for installation in corners

Specifications:

| |
|---|
| Fog performance, examples: 40 sec.: 230 m ³ 60 sec. + 4 min. pulse: 900 m ³ |
| 3 time settings from 140-400 m ³ |
| Optional pulse function (can shoot several times) |
| 0,4 l. fluid bag included |
| Enough fluid for 4 discharges in one container |
| Electronic fluid measurement |
| Power consumption: 1050 W |
| Mains connection: 230V, 50 Hz |
| Standby consumption after heating up: 60 W (on average) |
| Standby consumption when heat is disabled: 5-10 W |
| Heating time from cold: 8-10 min. |
| Re-heating time after fog discharge: 0-5 min. |
| Operating temperature (min./max.): 5/80° C. |
| Input: 5 signals |
| Output: 3 signals |
| On/off dipswitches for setting of fog time, signals and heating |
| Backup of electronics and pump (optional - batteries are not included as standard) |
| Power backup after power failure: Up to 1 hour (requires batteries) |
| Optical, audible and electrical signals/indicators |
| Status indicator on PCB |
| External status indicator |
| Anti-sabotage, impact-resistant steel casing |
| Colours available: White |
| Dimensions: L: 650, W: 140, H: 148 mm |
| Installation weight: 10 kg |

Printing errors excepted. Subject to changes to technical data.



SECURED IN SECONDS